



Code: 610 050 03  
6 PISTON PUMPS 50 LT.  
TYP 610

DECODING  
**610 050 03**

PUMP TYPE      DISPLACEMENT      ROTATION



**NOTE:** THE ABOVE SPECIFICATIONS REFER TO OIL TYPE ISO VG 46 AT 50°



Fluid Temp. °C	Input Pres. Bar	Optimale K. Viscosity	Oil Filtering
0 / 90	0,3 / 2 bar	10 / 100 cST	> 200 bar : 25 µm < 200 bar : 35 µm



**BIDIRECTIONAL PUMP**

**USED PLACED :**  
DUMPER TRUCKS  
PRIVATE AIM WINCHES  
TRACTOR LADLES

**NOTE:** TAKE A CONSIDERATION THAT OIL INLET TUBE CONNECTOR MUST BE VERTICAL POSITION & THE PUMP MUST BE 100 mm DISTANCE TO THE OIL TANK DURING TO ASSEMBLY. BEFORE STARTING THE PUMP BLEED THE AIR.



Code	Displacement cm <sup>3</sup> /1000	Rotation	Test Pressure 1	Test Pressure 2	Max. Test Pressure	Oil Inlet	Oil Outlet	Max. Con. Speed Rpm	Max. Inter. Speed Rpm	Weight	
610 050 03	49,5	Double	270	290	310	6 1" 1/4"	M22 1,5"	1700	1900	14,3	
			Test Pressure 1 : 60 sec.			Test Pressure 2 : 15 sec. Max.			Max Test Pressure : 5 sec. Max.		