

25 SERIAL GEAR PUMP



UNI

DECODING
XXX XXX XX

PUMP TYPE


DISPLACEMENT

ROTATION



Fluid Temp. °C	Input Pres. Bar	Optimale K. Viscosity	Oil Filtering
0 / 100	0,3 / 1,7 bar	10 / 100 CST	> 200 bar : 25 µm < 200 bar : 35 µm

RIGHT DIRECTIONAL PUMP





LEFT DIRECTIONAL PUMP

NOTE : THE ABOVE SPECIFICATIONS REFER TO OIL TYPE ISO VG 46 AT 50°

NOTE : SEE TECHNICAL PAGE TO CHANGE THE DIRECTION OF ROTATION

USED PLACED :
DUMPER TRUCKS
PRIVATE AIM WINCHES
TRACTOR LADLES



Code	Displacement cm ³ /2000	Rotation	Test Pressure	Max. Test Pressure	A	B	Oil Inlet	Oil Outlet	Max. Con. Speed Rpm	Max. Inter. Speed Rpm	Weight
250 025 01	25,8	Right	220	240	163	112	6 1"	6 3/4"	2450	2500	10
250 025 02	25,8	Left	220	240	163	112	6 1"	6 3/4"	2450	2500	10
250 035 01	35,4	Right	215	235	170	115	6 1"	6 3/4"	2450	2500	10,5
250 035 02	35,4	Left	215	235	170	115	6 1"	6 3/4"	2450	2500	10,5
250 045 01	45,2	Right	200	220	178	118	6 1"	6 3/4"	2400	2500	11
250 045 02	45,2	Left	200	220	178	118	6 1"	6 3/4"	2400	2500	11

Test Pressure : 60 sec

Max Test Pressure : 5 sec. Max.