


Code: 910 080 03
9 PISTON PUMPS 80 LT.
TYP 910

DECODING
910 080 03

PUMP TYPE

DISPLACEMENT

ROTATION



NOTE: THE ABOVE SPECIFICATIONS REFER TO OIL TYPE ISO VG 46 AT 50°



Fluid Temp. °C	Input Pres. Bar	Optimale K. Viscosity	Oil Filtering
0 / 90	0,3 / 2 bar	10 / 100 cST	> 200 bar : 25 µm < 200 bar : 35 µm



BIDIRECTIONAL PUMP

USED PLACED :
DUMPER TRUCKS
PRIVATE AIM WINCHES
TRACTOR LADLES

NOTE: TAKE A CONSIDERATION THAT OIL INLET TUBE CONNECTOR MUST BE VERTICAL POSITION & THE PUMP MUST BE 100 mm DISTANCE TO THE OIL TANK DURING TO ASSEMBLY. BEFORE STARTING THE PUMP BLEED THE AIR.



Code	Displacement cm ³ /1000	Rotation	Test Pressure 1	Test Pressure 2	Max. Test Pressure	Oil Inlet	Oil Outlet	Max. Con. Speed Rpm	Max. Inter. Speed Rpm	Weight
910 080 03	80,5	Double	280	300	320	G 1" 1/4"	G 1"	1800	2000	18
			Test Pressure 1 : 60 sec.		Test Pressure 2 : 15 sec. Max.		Max Test Pressure : 5 sec. Max.			